

Please answer below questions and email it to info@supply59.com

Supply59 Inc. CSST Trained Installer Test Certification

Become a certified **Supply59 CSST Trained Installer** by completing our **True or False** assessment.

To pass, you must correctly answer **all 16 True or False questions**.

All answers can be found in the official [**Supply59 Online Installation Manual**].

Score 100% to receive your personalized certification card.

This certification confirms your successful completion of the training and authorizes you to install the Supply59 **CSST system** in compliance with industry standards and safety regulations.

First Name:

Last Name:

Gas Certification Number:

Are you currently a CSST certified installer?

If yes, please specify which CSST system?

1. Supply59 CSST Maximum working pressure is five pounds per square inch 25 PSI.

True

False

2. Supply59 tubing must be protected in locations where it is concealed and constrained and within three inches of a nailing surface.

True

False

3. When Supply59 is concealed within a wall cavity it must be secured to the wall stud along the entire length.

True

False

4. Supply59 CSST require pressure test after installation.

True

False

5. Where a conflict exists between the design & installation manual and the local plumbing/ mechanical code, local code requirements shall take precedence.

True

False

6. Supply59 CSST must be bonded, and properly grounded by a qualified professional.

True

False

7. The Supply59 CSST fittings can be used more than once.

True

False

8. Supply59 CSST bonding conductor must be not smaller than a 6 AWG copper wire.

True

False

9. Supply59 CSST bonding conductor must not be longer than 75 feet.

True

False

10. Supply59 tubing can be buried underground or in concrete without a waterproof non-metallic sleeve.

True

False

11. Supply59 tubing must not be used as an appliance connector for portable appliances such as dryers and ranges.

True

False

12. Supply59 CSST can't be bond from the CSST pipe.

True

False

13. Supply59 CSST fittings have been certified and approved by CSA for use in concealed locations.

True

False

14. Supply59 CSST may be routed directly to stationary appliances such as water heaters and furnaces without using termination fittings.

True

False

15. Supply59 CSST temperature working Range is -20 to 150 degree.

True

False

16. Supply59 CSST can be bond from the CSST fitting only.

True

False

I have read, and agree to follow, the installation practices contained in the Supply59 CSST System Installation Manual. I am a Qualified Installer as defined by the local authority where Supply59 CSST is to be installed.

Signature:

Date:

Name:
